

MS 400 B Detector base with Bosch logo



The detector head is installed in the Detector Base MS 400.

The base is suitable for surface-mounted cable feeds as well as for flush-mounted cable feeds, and has separate attachment points for ceiling mount/flush-mounted back boxes. In addition, it fits all standard bore patterns.

The base made of white ABS plastic has a matte finish and seven terminal screws to connect the detector and its features to the fire panel.

Contacts connected to the terminals guarantee a secure electric connection when the detector module is installed. Cables up to 2.5 mm² in diameter can be used.

To protect against unauthorized removal, the detector head can be secured with a variable locking.

System overview

Connections	Power supply (0 V, +V)
	LSN (a1/a2, b1, b2)
	C-point
	Shielding

- ▶ Screw terminals for safe and secure electrical connection
- ▶ Locking against unauthorized detector removal
- ▶ Cable feed allows for surface or flush mounting
- ▶ Branded with Bosch logo

Parts included

Quantity	Component
1	Detector base with Bosch logo

Technical specifications

Material	Plastic
Color (RAL)	White, similar to RAL 9003
Dimensions (Ø x H) (mm)	120 mm x 22.7 mm
Weight (g)	72 g

Ordering information

MS 400 B Detector base with Bosch logo

Bosch-branded detector base for surface mounted and flush-mounted cable feed

Order number **MS 400 B**

Accessories

FAA-420-SEAL Damp room seal, 10 pcs

Damp room seal

Delivery unit is 10.

Order number **FAA-420-SEAL**



<https://www.boschsecurity.com>